



Technical Specifications

<p>Specifications</p>	<p>CSST: Stainless Steel 304 (ASTM A240) Fittings: Chrome-Plated Brass 3771 Gasket: High Quality EPDM Working Pressure: Up to 125 psig Intermittent Impulse Pressure: Up to 180 psig Temperature: -40°F to 180°F Minimum Bend Radius: 2.5" 100% Leak Tested</p>
<p>Certifications & Approvals</p>	<p>   </p> <p>IAPMO/UPC Certified ASME A 112.18.6 / CSA B125.6 NSF 61 Compliant AB 1953 Compliant: LEAD FREE</p>
<p>Sizes</p>	<p>3/4" ID 1" ID 1-1/4" ID 1-1/2" ID 2" ID</p>
<p>Lengths</p>	<p>12" 15" 18" 24" 36" 48"</p>
<p>Fittings</p>	<p>3/4" FIP x 3/4" FIP, 3/4" MIP, 3/4" Push-Fit, 1" FIP, 1-1/4" FIP 1" FIP x 1" FIP, 1-1/4" FIP 1-1/4" FIP x 1-1/4" FIP 1-1/2" FIP x 1-1/2" FIP 2" FIP x 2" FIP</p>
<p>Applications</p>	<p>Boilers Water Heaters Tankless Water Heaters</p>